

### TR-MAX4-C2D/C2Q

TR-MAX4-C2D/C2Q Industrial Computer w/ TR-980 SBC



### Reliable Industrial PC with TR-980 Single Board Computer For Trouble Free Operation and Ease of Service

TR-MAX4-C2D/C2Q desktop or panel mount PC has robust industrial design, built from only top-quality, industrial-grade components. The new PC has 6 slot backplane ISA/PCI expansion slots and strong rigid structure of the metalchassis. The chassis, as well as all components, are RoHS Compliant. It can be used as a vertical tower, horizontal PC or a panel mount PC.

TR-980 Single Board Computer guarantees compatibility with ISA and PCI option cards. Dual Channel Memory bus doubles the data rate up to 6.4Gb/s. The SBC supports remote wake up on LAN and modem. The Boot Agent for both RPL and PXE protocols is integrated into system BIOS.

Designed for use in power utilities, industrial process control and automation, the TR-MAX4 PC can be configured with a variety of power supply options: 110/220 VAC or 12, 24, 48, 125, 250 VDC. Excellent cooling and air flow characteristics ensure long-term reliability.

Powered by Intel 3.0GHz Intel Core 2 Duo or Core 2 Quad processors, this system can be supplied with a full-size CD/DVD-RW, floppy drive and optional solid state drive. Two hard drives can be included with RAID1 ATA100 controller for redundant operation. Easily replaceable front fan filter protects system in dusty environments.

Standard features include 2 serial ports (one is RS232/422/485 selectable), printer port, 3 USB ports and SVGA output. Dual Intel Gigabit Ethernet controller on board boost networking throughputs to 4 Gb/s.

TR-MAX4-C2D/C2Q is compatible with all versions of QNX, LINUX and Windows, including Windows 7. Available versions: the rubber feet (installed vertically or horizontally) and Panel mount.

The PC is expandable to adapt to client requirements. Actual MTBF > 100,000 hours, 3 years warranty.

Longevity: guaranteed supply until 2017. Always in stock.

Also check the TR-MAX4-P4 and TR-MAX4-PCIe

### TR-MAX4-C2D/C2Q

TR-MAX4-C2D/C2Q Industrial Computer w/ TR-980 SBC

#### Specification

##### Model

- TR-MAX4-C2D/C2Q Industrial desktop or panel mount computer

##### Processor

- 3.00GHz Intel Core 2 Duo or Core 2 Quad processor

##### Memory

- 2 x 184-pin DIMM sockets
- Max capacity: up to 4GB DDR

##### Expansion Slots

- Six slot backplane with one PICMG CPU card
- 2 x PCI, 3 x ISA, 1 x SBC, 2 ISA with bus-master control or 6 x ISA slots

##### Drive Bay

- 2 x 3.5" HDD (RAID1 OK) or flash solid state disk
- 1 x 3.5" floppy drive bay
- 1 x 5.25" DVD-ROM/CD-R/W

##### SVGA

- Intel 82865G 16MB 1600x1200 x 32-bit @ 60Hz

##### Ethernet

- 2 x Intel Pro 100/1000+ Mbps Fast Ethernet ports with throughput up to 4Gb/s

##### Solid State Drive

- Supports high speed Flash SSD up to 256GB

##### Watchdog Timer

- 1 ~ 256sec

##### Air Flow

- Optimized air flow with 62CFM (card cage) and 43CFM (power supply) quality NIDEC fans. Adaptive speed fan control. Adaptive temperature controller installed on air chamber support for minimal intake of dust

#### I/O

- 1 x external SVGA DB15 port
- 2 x serial RS-232 ports (422/485)
- 1 x parallel printer port
- 1 x bootable front USB port
- 2 x rear access USB ports
- 2 x RJ-45 LAN ports
- PS/2 keyboard/mouse connectors

#### Operating Temperature

- 0 ~ 50°C (32 ~ 122°F)

#### Humidity

- Relative 5 ~ 85%

#### System Monitor

- Features include processor temperature, system temperature and DC power voltages

#### Humidity

- Relative humidity 10 ~ 90%, non-condensing

#### Power Supply

- Output rating - 300W
- Input voltage - 100~240VAC @ 47/63Hz
- Optional DC input power - 12V, 24V, 48V, 125V and 250V
- MTBF - 100,000 hours
- Safety - ULC/FCC/CE compliant

#### EMI

- Compliant with FCC Class B

#### OEM Specifications Welcomed

#### Warranty

- 3 years

#### Additional Options

- Solid Flash SATA drive up to 256GB
- SATA RAID1 option - Promise SATA RAID controller and two Seagate 7200RPM Barracuda hard drives
- DC power supply option - 12V, 24V, 48V, 125V and 250VDC 150W

Compatible with QNX, LINUX, all versions of Microsoft Windows 2000, XP, VISTA and 7.

Also see TR-MAX4-PCIe with PCIe expansion slots.