

Transduction

TR-1000VA-48VDC

2U Rack Mount Power Inverter

TR-1000VA-48VDC DC to AC Sinewave



Features

- ▶ Pure sinewave output (<2%THD).
- ▶ Input and output isolation.
- ▶ High efficiency 87% ~ 90%.
- ▶ High surge capacity inductive loads.
- ▶ Soft start technology.
- ▶ Frequency 50/60Hz switchable.
- ▶ Auto restart.
- ▶ 2U rack mount.
- ▶ 3 year warranty.

Transduction

2U Rack Mount Power Inverter

TR-1000VA-48VDC

Specification

Model

- ▶ TR-1000VA-48VDC

DC Input Voltage

- ▶ 48VDC

Voltage Range

- ▶ 42-64VDC

Output Wave Form

- ▶ Pure sinewave <2%THD

AC Output Voltage

- ▶ 120VAC

Continuous Output Power

- ▶ 1000W

Max Peak Power

- ▶ 2400W

Frequency

- ▶ 50/60Hz $\pm 3\%$

AC Regulation

- ▶ $\pm 5\%$

Receptacles

- ▶ 2 front, 2 rear

Indicators

- ▶ Analog 2.5" V & A meters

DC Current

- ▶ 20A, 80A in-rush

No Load Current Draw

- ▶ 0.3A

Efficiency

- ▶ >87%

DC Connector

- ▶ Terminal lugs and 40" cables

Battery Low Alarm

- ▶ 44 $\pm$ 2V

Battery Low Shutdown

- ▶ 42 $\pm$ 2V

Over Voltage

- ▶ 64 $\pm$ 2V

Temperature Protection

- ▶ 55°C $\pm$ 5°C

Output Short Circuit Protection

- ▶ Shutdown

Input Reverse Polarity Circuit Protection

- ▶ Internal fuse

Overload Protection

- ▶ Restarts 2 times. Shutdown if failed

Operating Temperature

- ▶ 0°C ~ 50°C

Humidity

- ▶ 20% ~ 90% RH, non-condensing

Storage Temperature Range

- ▶ -30°C ~ 70°C; 10% ~ 95% RH

Temperature Coefficient

- ▶ $\pm 0.05\%$ /°C (0°C ~ 50°C)

Dimensions

- ▶ 17"(L) x 19"(W) x 3.5"(H)

Net Weight

- ▶ 9.0KG

TR-1000VA-48VDC DC to AC Sinewave