

Transduction

TR-5190

TR-5190 TFT LCD Industrial PC w/ Touch Screen



Reliable 19" Workstation with Single Board Computer for trouble free operation and ease of service

TR-5190 NEMA 4 Panel Mount or Rack Mount PC with 19" LCD Touch Screen

This new PC offers 19" bright (250 cd/m² with contrast ratio 750:1) TFT LCD display with touch screen capability and has 6 backplane ISA/PCI expansion slots. Panel mount version is easily installed on panels with (no studs) TR-Fastclips. An 8U rack mount version is also available.

Designed for use in power utilities, industrial process control and automation, the TR-5000 series panel PC/display can be configured with a variety of power supply options: 110/220 VAC or 12, 24, 48, 125, 250 VDC.

Powered by Intel Pentium 4 or Celeron processors with 800 Mhz FSB, this system can be supplied with slim CD-ROM* and optional solid state drive. Two hard drives can be included with optional RAID1 ATA100 controller for redundant operation.

*Slim DVD-ROM/CD-RW drive option is available.

Standard features include 2 x 100/1000 Mbps Ethernet ports, 2 serial ports, printer port and 2 USB ports. Also features both internal LVDS and external SVGA ports that can operate at the same time.

TR-5190 is compatible with all versions of LINUX and Windows. QNX version is also available. 3 year warranty. Delivery is from stock.

Transduction

TR-5190

TR-5190 TFT LCD Industrial PC w/ Touch Screen

SPECIFICATIONS:

- **Panel Mount & Rack Mount Industrial PC**
 - **NEMA 4 Steel baked epoxy black front panel**
Optional NEMA 4 Stainless Steel
 - **Processor:** Socket 478 for Intel Pentium 4 or Celeron up to 3.6GHz with 800MHz FSB
Support for Hyper Threading
 - **19.0" TFT LCD Display:**
Resolution 1280x1024 (XGA)
Backlight MTBF: 50,000 hours
Brightness: 250 cd/m²
Contrast ratio: 750:1
Resistive touch screen - USB
 - **System Memory:**
2x184-pin DIMM sockets
Max capacity: Up to 2GB DDR
 - **Expansion slots:**
Seven slot backplane with one PICMG CPU card
4 PCI, 2 ISA, 1 SBC
 - **Drive Bay:**
2 x 3.5" HDD (RAID1 OK) or Flash Solid State Disk
1 x 5.25 Slim size CD-ROM
or 1 x 5.25 Slim DVD-ROM /CD-RW
 - **SVGA:** 82865GV 16MB
1600 x 1200 x 32-bit @ 60Hz
 - **Ethernet:**
2 x Intel Pro 100/1000+ Mbps Fast Ethernet ports
 - **SSD:** Supports high speed Flash SSD up to 128GB
 - **Watchdog timer:** 1 ~ 256 sec
 - **Air Flow:** Optimized air flow with 62 CFM (card cage) and 43 CFM (power supply) quality NIDEC fans
 - **IO:**
1 x internal XGALVDS
1 x external SVGA DB15
2 x Serial RS-232
1 x Parallel
2 x USB 2.0
2 x RJ-45 LAN Jack
PS/2 Keyboard/mouse connectors
 - **Software Compatibility:**
LINUX and all versions of Microsoft Windows
QNX version with ATI RADEON SVGA is also available
 - **Power Supply:**
Output rating: 300W
Input voltage: 100~240VAC @ 47/63Hz
Optional DC input power: 12V 24V, 48V, 125V, 250V
MTBF: 80,000 hrs
Safety: UL/cUL/TUV/FCC/CE approved
 - **System Monitor** features include processor temperature, system temperature & DC power voltages
 - **Chassis Colors:** Black, OEM color optional
 - **Environmental Specifications:**
Operating Temperature: 0° ~ 50°C (32 ~ 122° F), 60C (140F) for 2 hours
Relative Humidity: 5 ~95%
 - **OEM Specifications Welcomed**
 - **Dimensions:**
W. 17.75" x H. 15.25" x D. 6.4" (D. 8.00" behind front panel)
Rack mount version is 8U high
N.W. 32 lbs, G.W. 37 lbs, CUFT 6
 - **Warranty: 3 years**
- Additional Options Available:**
- 8U Rack Mount version
Allows the TR-5190 to be mounted in a standard 19" rack configuration, includes 3 USB ports
NOTE: Rear Access CD is used when using the Rack Bracket version
 - Rear Access Floppy/CD Option
Provides 3 rear accessible drive bays:
1 x 5.25" for slim 24x CD-ROM
2 x 3.5" for Floppy Drive and Hard Drive
 - 64 ~ 512GB high speed Flash SATA SSD
 - SATA RAID1 Option
PD3500 RAID controller and two Seagate 7200RPM Constellation hard drives
 - DC Power Supply Option
300W DC 12, 24, 48, 125, 250V
 - Slim DVD-ROM 8x / CD-RW 24x24x24 drive instead of slim 24x CD-ROM
- Order:**
- TR-5190-PM Panel Mount version
 - TR-5190-RM Rack Mount version
 - TR-2USB-1U 2x external USB rack mount ports