


Transduction

ATX Core 2 Quad Motherboard

TR-ATX-Q35

TR-ATX-Q35 Industrial Motherboard



Features

- ▶ Accepts Intel Core 2 Quad, Core 2 Duo, Celeron D processors in LGA775 package.
- ▶ Four DDR2-800 DIMM sockets for up to 8GB system memory in Dual Channel Mode.
- ▶ Dual GbE LAN's for maximum communication bandwidth.
- ▶ Multiple I/O functions: 10 x USB2.0, 4 x COM ports, 6 x SATA, IRDA, 1 x PRIDE, 1 x CF, 1 x LPT, 1 x FDD.
- ▶ Six SATA-II ports with RAID0, RAID1, RAID5, and RAID10.
- ▶ Five PCI-32 bits slots, One PCI-EX16, One PCI-EX4.
- ▶ Long-term supply item, not a "seasonal" product.
- ▶ 3 years warranty + 10% for 5 years.

TR-ATX-Q35

Specification

Processor

- ▶ Intel Core 2 Quad, Core 2 Duo, Celeron D processor.
- ▶ Supports Front Side Bus speed 800, 1066 or 1333MHz.

Processor Socket

- ▶ LGA 775 Socket

Chipset

- ▶ Intel Q35 and ICH9DO chipset.

Memory

- ▶ 4 DDR2 DIMM sockets with Dual Channel Mode support.
- ▶ DDR2 667/800 non-ECC memory up to 8.0GB.

BIOS

- ▶ Award Standard PnP Flash BIOS 6.0 on 8Mbit FlashROM with BootBlock for Fail-Safe.

10/100M/1000M Ethernet

- ▶ Two Realtek RT8111C Dual Gb LAN.
- ▶ Wake-on-LAN, Remote Boot with PXE and RTL.

Video

- ▶ Intel Q35 Integrated GMA3100 Graphic Engine.

PCI/PCI-Express

- ▶ Five PCI 5v/32-bits slots.
- ▶ One PCI-Ex16 slots for high-end graphics cards.
- ▶ One PCI-Ex4 slots for PCIE cards.

SATA and PIDE

- ▶ Six SATA-I/II ports with RAID0, RAID1, RAID5, RAID10.
- ▶ One USB bridged PIDE controller, up to UltraDMA mode 5.
- ▶ One standard 40-pins box header to support 3.5"HDD or DVD.
- ▶ One CF-II socket supports all types CF cards.

On Board I/O

- ▶ Winbond 83627HF LPC I/F Super I/O chip.
- ▶ Four serial ports as COM1 ~ COM4. COM2 is RS232/422/485 selectable by jumper.
- ▶ One Parallel port supports SPP/ECP/EPP mode.
- ▶ One IrDA port, One Floppy connectors for up to two drives.

Audio

- ▶ RealTek ALC888 High-Definition Audio chip on-board.

Watch-Dog Timer

- ▶ Programmable watchdog timer from 1~255 seconds.

Form Factor

- ▶ Standard Full-Size ATX form factor.
- ▶ 9.6"(L) x 12"(W); or 244mm (L) x 305mm (W)

Power

- ▶ One standard ATX 24-pins power connector
- ▶ One ATX-12V 8-pins connector for CPU power.
- ▶ Support both AT and ATX mode.

Operating Temperature

- ▶ 0 to 60°C operating range.
- ▶ Relative Humidity: 5~95%, non-condensing.

Compatible with Windows 2K, Vista, Linux & DOS 6.22.

Warranty: 3 years +10% for 5 years