

TR-OBELISK

"THE MEDIUM IS THE MESSAGE"

Transduction manufactures high performance LCD displays for messaging kiosks, digital signage and advertising with wide range of flexibility. With HD and UHD capability your audience can revel in pure, expressive hues thanks to accurate, true-to-life color reproduction and high fidelity sound. Our vertical displays are highly reliable due to years of experience with industrial computers and monitors. Our vertical TR-OBELISK series display will give you many years of trouble free operation.

Features

- Screen size 55".
- HD and UHD brilliant colors.
- Free remote software.
- Front and back options.
- Viewing angle - 178 degrees.
- Brightness - 450 to 2700 cdm.
- Optional multi-touch screen.
- Surface hardness 7H.
- Optional wireless access.
- Extended temperature outdoor option.
- Various cable access options.
- High security sturdy steel enclosure.
- Flexibility of customization.
- Universal AC power supply.
- ISO 9001:2008 Quality Assurance.
- 3 years warranty with rapid exchange of parts.
- Sold via full service dealers.
- TR-OBELISK-55HD vertical HD display.
- TR-OBELISK-55UHD vertical UHD display.



TR-OBELISK

Specification

Model

- TR-OBELISK55HD floor standing touch screen kiosk display

Size

- 55"

Panel Brand

- LG/Samsung

Resolution

- 1920 x 1080

Display Ratio

- 16:9

Brightness

- 550cdm

Contrast

- 1000:1

Color

- 16:7

Response Time

- 4ms

Backlight Life

- > 60,000 hours

Viewing Angle

- 178°/178°

Touch

- IR multi-points touch panel

Transmittance

- >98%

Touch Panel Response Time

- <16ms

Surface Hardness

- 7H

Touch Manner

- Unlimited

Wheels

- Customizable

Enclosure

- Cold-rolled steel with fine car paint

Color

- Coffee color/white+black

CPU

- RK3188 ARM Cortex A9 Quadcore

Operating System

- Android 4.4.2

Memory

- 2GB DRR3

Nand Flash

- 8GB

SD Card

- Max. support 32GB

Power Supply

- 300W, 110V-240VAC, 50/60Hz

Operating Temperature

- -20 ~ 60°C (-4 ~ 140°F)

Storage Temperature

- -20 ~ 70°C (-4 ~ 158°F)

Humidity

- Relative humidity 20 ~ 80%, non-condensing

Weight

- 60kg (132lbs)

Warranty: 3 years with technical support for life